

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An electrically ~~Electrically~~ operated equipment comprising:

an environmentally sealed enclosure having at least one wall permeable to inductive magnetic flux;

an electric circuitry environmentally protected within the enclosure; and

a magnetic field generator within the enclosure and interconnected to the electrically operated circuitry to produce a magnetic flux indicative of a state of operation of the circuitry, the flux, after passage through the permeable wall, to induce an electrical current in a magnetic flux sensor outside the enclosure, and produce a visual indication of the state of operation of the electric circuitry.

2. (Currently Amended) The electrically ~~Electrically~~ operated equipment comprising:

an environmentally sealed enclosure having at least one wall permeable to magnetic flux;

an electric circuitry environmentally protected within the enclosure;

a magnetic field generator within the enclosure and interconnected to the electric circuitry for producing a magnetic flux indicative of a state of operation of the electric circuitry, said magnetic flux to pass through the permeable wall;

a magnetic flux sensor positioned outside the enclosure to be influenced by the magnetic flux, thereby to induce an electrical current corresponding to the magnetic flux;
and

a visual indicator positioned outside the enclosure and electrically connected to the sensor and controllable by the electrical current to produce a visual indication of the state of operation of the electric circuitry.

3. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 2, wherein the electric circuitry comprises an electronic circuitry.

4. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 2, wherein the electric circuitry comprises a power circuitry.

5. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 2, wherein the magnetic field generator comprises a magnetically permeable core with an electrically conductive coil wound onto the core.

6. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 2, wherein the magnetic flux sensor and the visual indicator are mounted upon the enclosure.

7. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 2, wherein the magnetic flux sensor and the visual indicator are both environmentally sealed.

8. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 2, wherein the magnetic flux sensor and the visual indicator are both sealed within a common carrier and are electrically interconnected for electrical current transmission within the common carrier.

9. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 8, wherein the magnetic flux sensor comprises an electrically conductive coil.

10. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 9, wherein the electrically conductive coil of the magnetic flux sensor is wound around a permeable core.

11. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 9, wherein the electrically conductive coil of the magnetic flux sensor is wound around an air core.

12. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 8, wherein the common carrier has a front and a rear and comprises a multi-layer structure with the adjacent layers environmentally sealed together, and with the magnetic flux sensor and the visual indicator each carried by an inner layer of the multi-layer structure, and with the visual indicator visible, when operated, from in front of the common carrier.

13. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 12, wherein the visual indicator projects forwardly from a front surface of its carrier layer and a spacer inner layer is attached adhesively to the front surface of the carrier layer, the spacer layer defining a space into which the visual indicator extends.

14. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 12, wherein the magnetic flux sensor projects in at least one direction away from its carrier layer and a spacer inner layer is attached adhesively to the appropriate surface of the carrier layer, the spacer inner layer defining a space into which the magnetic flux sensor extends.

15. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 12, wherein the multi-layer structure comprises a support layer positioned rearwardly of the magnetic flux sensor and the visual indicator.

16. (Currently Amended) An electrically operated equipment comprising:

an environmentally sealed enclosure having at least one wall permeable to a magnetic flux;

electric circuitry comprising electronic telecommunications circuitry and electrical power circuitry environmentally protected within the enclosure;

each circuitry having an individual magnetic field generator within the enclosure, each individual magnetic field generator interconnected to its associated circuitry for producing a magnetic flux indicative of a state of operation of the associated circuitry, said magnetic flux to pass through the permeable wall;

an individual magnetic flux sensor associated with each magnetic field generator, each magnetic flux sensor positioned outside the enclosure to be influenced by the magnetic flux from the associated magnetic field generator to induce ~~[[and]]~~ an electrical current corresponding to the magnetic flux; and

an individual visual indicator associated with each magnetic flux sensor, each visual indicator positioned outside the enclosure, electrically connected to the associated magnetic flux sensor and controllable by the electrical current induced at its sensor to produce a visual indication of the state of operation of the associated electric circuitry.

17. (Currently Amended) The electrically operated equipment ~~Equipment~~ according to claim 16, wherein all magnetic flux sensors and all visual indicators are environmentally sealed within a common carrier and each visual indicator is electrically connected to its associated magnetic flux sensor for signal transmission within the common carrier, the common carrier being permeable to the magnetic flux to enable each magnetic flux sensor to sense the magnetic flux from its associated magnetic flux generator.

18. (Currently Amended) A visual indication device for indicating a state of operation of electrically operated equipment comprising: ~~[[--]]~~

a magnetic flux sensor capable of being influenced by a magnetic flux to induce an electrical current in the sensor corresponding to the magnetic flux;

a visual indicator electrically interconnected to the magnetic flux sensor and controllable by the induced electrical current to produce a visual indication of a state of operation of the electrically operated equipment; and

a common carrier, the magnetic flux sensor and the visual indicator being environmentally sealed within the common carrier and electrically interconnected within the common carrier.

19. (Currently Amended) The [[A]] device according to claim 18, wherein the magnetic flux sensor comprises an electrically conductive coil.

20. (Currently Amended) The [[A]] device according to claim 19, wherein the electrically conductive coil of the magnetic flux sensor is wound around a permeable core.

21. (Currently Amended) The [[A]] device according to claim 19, wherein the electrically conductive coil of the magnetic flux sensor is wound around an air core.

22. (Currently Amended) The [[A]] device according to claim 18, wherein the common carrier has a front and a rear and comprises a multi-layer structure with adjacent layers of the structure environmentally sealed together, and with the magnetic flux sensor and the visual indicator each carried by an inner layer of the multi-layer structure, and with the visual indicator visible, when operated, from in front of the common carrier.

23. (Currently Amended) The [[A]] device according to claim 22, wherein the visual indicator projects forwardly from a front surface of its carrier layer and a spacer inner layer is attached adhesively to the front surface of the carrier layer, the spacer layer defining a space into which the visual indicator extends.

24. (Currently Amended) The [[A]] device according to claim 22, wherein the magnetic flux sensor projects in at least one direction away from its carrier layer and a spacer inner layer is attached adhesively to the appropriate surface of the carrier layer, the spacer inner layer defining a space into which the magnetic flux sensor extends.

25. (Currently Amended) The [[A]] device according to claim 22, wherein the multi-layer structure comprises a support layer positioned rearwardly of the magnetic flux sensor and of the visual indicator.

26. (Previously Presented) A method of visually indicating an operational state of an electric circuitry which is environmentally sealed within an environmentally sealed enclosure comprising:

producing a magnetic flux within the enclosure, the magnetic flux indicative of the state of operation of the electric circuitry;

passing the magnetic flux through a flux permeable wall of the enclosure, to the outside of the enclosure; and

on the outside of the enclosure, sensing the magnetic flux, inducing the sensed flux into a corresponding electrical current and, with the electrical current, operating a visual indicator to indicate the state of operation of the electric circuitry.